



True-Color Auto Darkening Filter

- CE Classification is #3/9 & #3/10 = 1/1/1/1, #3/11 & #3/12 = 1/1/1/2: Accuracy of Vision, Diffusion of Light, Consistent Shade, Angular Dependence
- Clear True-Color Blue HD Technology
- Solar Cell and Non-Replaceable Lithium Battery
- Enhanced visible spectrum, optimal clarity
- Reduced eye and neck fatigue
- 2 Independent Arc Sensors. Thickness 5.5 mm / 0.2"
- Auto-on / Auto-off circuitry
- Viewing area of 5.15 square inch. 3.62" x 1.42"
- Switching speed 3/10,000 sec (0.3 ms)
- Start in shade 3-grind mode



11122

2 cover lens included

2 Year Warranty

Meets ANSI Z87.1, CSA Z94.3, CE EN 379 Standards

UPC	Size	Filter Fixed	View Area	Description	CE Classification	Retail QTY*	Retail Pack	Master Pack
11121	2" x 4.25"	9	3.62" x 1.42" (5.15 sq in)	True-Color	1/1/1/1	1	10	20
11122	2" x 4.25"	10	3.62" x 1.42" (5.15 sq in)	True-Color	1/1/1/1	1	10	20
11123	2" x 4.25"	11	3.62" x 1.42" (5.15 sq in)	True-Color	1/1/1/2	1	10	20
11124	2" x 4.25"	12	3.62" x 1.42" (5.15 sq in)	True-Color	1/1/1/2	1	10	20

* Sold in units of 1

Instruction For Use

- » Install the filter and protective plate into the suitable welding helmet.
- » The solar cell and light sensor must be fully exposed and be sure the arc light can be received fully by solar cell and sensor.
- » Then strike the arc, the filter will darken immediately.



Warnings

- » Replace damaged parts to avoid serious injury.
- » Avoid heavy knock to break the filter.
- » Do not immerse filter into water or other liquid.
- » Use only at 14° F (-10° C) - 149° F (65° C).
- » If the filter is not to be used for a long period of time, pack the filter in the box or store in a dark place.
- » Storage temperature is -4° F (-20° C) -185° F (85° C).

Weldcote Sales & Corporate Offices:

842 Oak Grove Rd., Kings Mountain, NC 28086 USA
phone: 877-866-4115, 704-739-4115, fax: 704-739-6116

Weldcote Warehouse & Sales:

1930 S. Carlos Ave., Ontario, CA 91761
phone: 866-923-2167, fax: 909-923-7016

Weldcote Abrasive & Manufacturing Dist. Center & Training:

7720 Lehigh Ave. Niles, IL 60714
phone: 224-998-2600, 888-258-0121, fax: 224-998-2649

Weldcote Distribution & Sales:

5994 Griggs Road, Houston, TX 77023