

# 2300 Phosphor Bronze Electrodes



## SAFETY DATA SHEET

Control # 540 date: 3/17/20

### SECTION: 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

- 1.1 Product Name: 2300 Phosphor Bronze Electrodes  
Product Identification: Flux Coated Phosphor Bronze electrode  
AWS A5.1
- Product Specification:
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:
- 1.2.1 Relevant identified uses: For welding consumables and related products.
- 1.2.2 Uses advised: Reference the [ 7. Handling and storage]
- 1.3 Details of the supplier of the safety data sheet:
- Supplier: Weldcote Metals Inc.  
842 Oak Grove Rd.  
Kings Mountain, NC 28086
- Emergency telephone number: (800) 424-9300 or (704) 739-4115
- Email: [info@weldcotemetals.com](mailto:info@weldcotemetals.com)

### SECTION: 2 HAZARDS IDENTIFICATION

- 2.1 Classification of the mixture:  
The product is placed on the market in solid form
- 2.1.1 Classification in accordance with GHS-US:
- 2.2 Label elements:  
GHS-US labeling

Hazard Pictograms (GHS-US):



Signal word (GHS-US): Danger

Hazard statements (GH5-US):

H315 Causes skin irritation

H319 Causes serious eye irritation

H335 May cause respiratory irritation

H400 Very toxic to aquatic life

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces – no smoking

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P264 Wash skin and hair thoroughly after handling

P271 Use only outdoors or in well ventilated area.

P273 Avoid release to the environment

P280 Wear protective gloves/eye protection/face protection

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P304+P340 F INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell

P332+P313 IF skin irritation occurs: Get medical advice/attention

P337+P313 IF eye irritation persists: Get medical advice/attention

P362 Take off contaminated clothing and wash before reuse.

P391 Collect spillage

P403+P233 Store in a well ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

2.3 Other hazards: No additional information available

2.4 Unknown acute toxicity (GHS-US): No data available.

**SECTION: 3 COMPOSITION/INFORMATION ON INGREDIENTS**

- 3.1 Substances: No data available  
Full text of H-phrases: see section 16
- 3.2 Mixtures: The mixture contains dangerous substances:

Substance name	Product Identifier (CAS No)	% Percent	GHS-US classification	
Copper	Cu	7440-50-8	70-80	Flam Sol. 1 H228, Aquatic Acute 1 H400
Barium Carbonate	CBaO <sub>3</sub>	513-77-9	1-11	Acute Tox. 4 H302
Sodium Silicate	Na <sub>2</sub> SiO <sub>3</sub>	1344-99-8	1-11	Skin corr. 1B H314, STOT SE 3 H335
Calcium Carbonate	CaO	1317-65-3	1-11	Not classified
Calcium Fluoride	CaF <sub>2</sub>	7789-75-5	1-11	Skin irrit. 2 H315, Eye irrit. 2A H319, STOT SE 3 H335
Graphite	C	7782-42-5	1-5	Not classified
Iron	Fe	7439-89-6	1-5	Acute Tox. 4 (Oral) H302
Tin	Sn	7440-31-5	1-11	Not classified

**SECTION: 4 FIRST AID MEASURES**

- 4.1 Description of first aid measures:
  - First-aid measures after inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and get medical attention.
  - First-aid measures after skin contact: Flush with water for at least 15 minutes. Seek medical attention if irritation develops or persists.
  - First-aid measures after eye contact: Immediately flush eyes with water and continue washing for at least 15 minutes. Obtain medical attention if discomfort persists.
  - First-aid measures after ingestion: Do NOT induce vomiting. Get immediate medical attention.
- 4.2 Most important symptoms and effects, both acute and delayed:
  - Symptoms/injuries after inhalation: Short-term (acute) overexposure to the gases, fumes, and dusts may include irritation of the eyes, lungs, nose, and throat. Some toxic gases associated with welding may cause pulmonary edema, asphyxiation, and death. Acute overexposure may include signs and symptoms such as watery eyes, nose and throat irritation, headache, dizziness, difficulty in breathing, frequent coughing, or chest pain. The presence of chromium/chromate in fume can cause irritation of nasal membranes and skin. The presence of nickel compounds in fume can cause metallic taste, nausea, tightness of chest, fever, and allergic reaction. Excessive inhalation or ingestion of manganese can produce manganese poisoning. Overexposure to manganese compounds may affect the central nervous system, symptoms of which are languor, sleepiness, muscular weakness, emotional disturbances, and spastic gait resembling Parkinsonism. These symptoms can become progressive and permanent if not treated. Excessive inhalation of fumes may cause "Metal Fume Fever" with Flu-like symptoms such as chills, fever, body aches, vomiting, sweating, etc.
  - Symptoms/injuries after skin contact: Dusts may cause irritation.
  - Symptoms/injuries after eye contact: Causes eye irritation.
  - Symptoms/injuries after ingestion: Not an anticipated route of exposure during normal product handling. May be harmful if ingested.
- 4.3 Indication of any immediate medical attention and special treatment needed: No data available.

**SECTION: 5 FIREFIGHTING MEASURES**

- 5.1 Extinguishing media:
  - Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire.
  - Unsuitable extinguishing media: No data available.
- 5.2 Special hazards arising from the substance or mixture: Fire may produce irritating or poisonous gases.
  - Fire hazard: Not flammable
  - Explosion hazard: None known
- 5.3 Advice for firefighters: In the event of fire, wear self-contained breathing apparatus and full protective gear.

**SECTION: 6 ACCIDENTAL RELEASE MEASURES**

- 6.1 Personal precautions, protective equipment and emergency procedures:  
For non-emergency personnel: Wear appropriate personal protective equipment as specified in Section 8. Ensure adequate ventilation.  
For emergency responders: No data available.
- 6.2 Environmental precautions: Avoid release into the environment. Avoid dispersal of spilled material and contact with soil, ground and surface water drains and sewers.
- 6.3 Methods and material for containment and cleaning up: Take up mechanically. Collect the material in labeled containers and dispose of according to local and regional authority requirements.
- 6.4 Reference to other sections: See Section 7 for information of safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

**SECTION: 7 HANDLING AND STORAGE**

- 7.1 Precautions and safe handling: Welding may produce dust, fumes and gases hazardous to health. Avoid breathing dust, fumes and gases. Use adequate ventilation. Keep away from sources of ignition. Avoid contact with skin, eyes and clothing. Do not eat, drink and smoke in work areas.
- 7.2 Conditions for safe storage, including and incompatibilities: Store in cool, dry and well-ventilated place. Keep away from incompatible materials. Keep away from heat and open flame.
- 7.3 Specific end use(s): For welding consumables and related products.

**SECTION: 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

- 8.1 Control parameters: Exposure limits were not established for this product

<b>Copper</b> (CAS No) 7440-50-8		
USA ACGIH	ACGIH (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	1 mg/m <sup>3</sup>
<b>Barium Carbonate</b> (CAS No) 513-77-9		
USA ACGIH	ACGIH (TWA) (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup>
<b>Sodium Silicate</b> (CAS No) 1344-09-8		
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	20 million parts per cubic ft
<b>Calcium carbonate</b> (CAS No) 1317-65-3		
USA ACGIH	ACGIH (TWA) (mg/m <sup>3</sup> )	15 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	10 mg/m <sup>3</sup>
<b>Calcium Fluoride</b> (CAS No) 7789-75-5		
USA ACGIH	ACGIH (TWA) (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2.5 mg/m <sup>3</sup>
<b>Graphite</b> (CAS No) 7782-42-5		
USA ACGIH	ACGIH (TWA) (mg/m <sup>3</sup> )	0.5 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	0.5 mg/m <sup>3</sup>
<b>Iron</b> (CAS No) 7439-89-6		
USA ACGIH	ACGIH (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
<b>Tin</b> (CAS No) 7440-31-5		
USA ACGIH	ACGIH (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>
USA OSHA	OSHA PEL (TWA) (mg/m <sup>3</sup> )	2 mg/m <sup>3</sup>

8.2 Exposure controls:

Appropriate engineering controls: local exhaust and general ventilation must be adequate to meet exposure standards.

Hand protection: Wear welding gloves.

Eye protection: Wear helmet or face shield with filter lens of appropriate shade number. See ANSI/ASC Z49.1 Section 4.2. Provide protective screens and flash goggles, if necessary, to shield others.

Skin and body protection: Wear head and body protection, which help to prevent injury from radiation, sparks, flame and electrical shock. See ANSI Z49.1. At a minimum this includes welder's gloves and a protective face shield, and may include arm protectors, aprons, hats, shoulder protection, as well as dark substantial clothing. Train the employee not to touch live electrical parts and to insulate him/herself from work and ground. Welders should not wear short sleeve shirts or short pants.

Respiratory protection: If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

**SECTION: 9 PHYSICAL AND CHEMICAL PROPERTIES**

9.1 Information on basic physical and chemical properties:

Physical state:	- Solid
Appearances:	- Rods
Color:	- Dark brown
Odor:	- No odor
Odor threshold:	- No data available
pH:	- No data available
Relative evaporation rate (butyl acetate = 1):	- No data available
Melting point:	- 850-1100 C (1560-2000 F)
Freezing point:	- No data available
Initial boiling point and boiling range:	- No data available
Flash point:	- No data available
Self ignition temperature:	- No data available
Decomposition temperature:	- No data available
Flammability (solid, gas):	- No data available
Vapour pressure:	" No data available
Relative vapour density at 20· C:	- No data available
Relative density:	- 6-9 g/cm3
Solubility(ies)	- No data available
Log Pow:	- No data available
Log Kow:	- No data available
Viscosity, kinematic:	- No data available
Viscosity, dynamic:	- No data available
Explosive properties:	- No data available
Oxidizing properties:	- No data available
Explosive limits:	- No data available

9.2 Other information: No additional information available.

**SECTION: 10 STABILITY AND REACTIVITY**

10.1 Reactivity: No additional information available.

10.2 Chemical stability: The product is stable under normal conditions. When using it may produce dangerous fumes and gases.

10.3 Possibility of hazardous reactions: Will not occur.

# SAFETY DATA SHEET

10.4 Conditions to avoid: None

10.5 Incompatible materials: None

10.6 Hazardous decomposition products: Welding fumes and gases cannot be classified simply. The composition and quantity of both are dependent upon the metal being welded, the process, procedure and welding consumables used. Other conditions which also influence the composition and quantity of the fumes and gases to which workers may be exposed include: coating on the metal being welded (i.e. paint, painting, galvanizing), the number of welders, the volume of the work area, the quality and the amount of ventilation, the position of the welders head with respect to the fume plume, as well as the presence of contaminants in the atmosphere (such as chlorinated hydrocarbon vapors from the cleaning and degreasing activities).

When an electrode is consumed, the fume and gas decomposition products generated are different in percent and form from the ingredients listed in Section 3. Fume and gas decomposition, and not the ingredients in the electrode, are important. The concentration of a given fume or gas component may decrease or increase by many times the original concentration. Also, new compounds not in the electrodes may form.

Decomposition products of normal operation include those originating from the volatilization, reaction or oxidation of the materials shown in Section 3, plus those from the base metal coating, etc., as noted above. Reasonable expected fume constituents of this product would include: Complex oxides of iron, manganese, silicon, chromium, nickel, columbium, molybdenum, copper, carbon dioxide, carbon monoxide, ozone and nitrogen Oxides. Some products will also contain antimony, barium, molybdenum, aluminum, columbium, magnesium, strontium, tungsten, and or zirconium. Fume limit for chromium, nickel and or manganese may be reached before limit of 5 mg/m3 of general welding fumes is reached.

Gaseous reaction products may include carbon monoxide and carbon dioxide. Ozone and nitrogen oxides may be formed by the radiation from the arc. Determine the composition and quantity of fumes and gases to which workers are exposed by taking an air sample from inside the welder's helmet if worn or in the worker's breathing zone. Improve ventilation if exposures are not below limits. See ANSI/AWS Fl.1, Fl.3 and Fl.5, available from the American Welding Society, 550 N.W. Lejeune Road, Miami, FL 33126.

**SECTION: 11 TOXICOLOGICAL INFORMATION**

11.1 Information on toxicological effects:

Acute toxicity: Harmful if swallowed

Substance name	CAS number	LD50 oral rat (mg/kg)	ATE (oral) (mg/kg)	Comments
Copper	7440-50-8	>2000 mg/kg	>2000 mg/kg	
Barium Carbonate	513-77-9	>418 mg/kg		
Sodium silicate	1344-09-8	1153 mg/kg	1153.000 mg/kg	
Calcium Carbonate	1317-65-3	>2000 mg/kg	>2000 mg/kg	
Calcium Fluoride	7789-75-5	> 2000 mg/kg	> 5070 mg/kg	
Graphite	7440-44-0	>440 mg/kg	>120 mg/kg	
Iron	7439-89-6	984 mg/kg	984,000 mg/kg	bodyweight
Tin	7440-31-5			No Data

Skin corrosion/irritation:	Not classified
Serious eye damage/irritation:	Not classified
Respiratory or skin sensitization:	May cause an allergic skin reaction.
Germ cell mutagenicity:	Not classified
Carcinogenicity:	May cause cancer
Reproductive toxicity:	Not classified
Specific target organ toxicity (single exposure):	Not classified
Specific target organ toxicity (repeated exposure):	Not classified
Aspiration hazard:	Not classified

**SECTION: 12 ECOLOGICAL INFORMATION**

12.1 Toxicity:

Ecology - general: Very toxic to aquatic life.

# SAFETY DATA SHEET

Copper (CAS No) 7440-50-8	
LC50 fishes 1	0.0068 - 0.0156 mg/l (Exposure time: 96 h - species: Pimephales promelas)
EC50 Daphnia 1	0.03 mg/l (Exposure time: 48 h - species: Daphnia magna[static])
EC50 other aquatic organisms 1	0.0426 - 0.0535 mg/l (Exposure time: 72 h - species: Pseudokirchneriella subcapitata[static])
LC50 fish 2	< 0.3 mg/l (Exposure time: 96 h - species: Pimephales promelas ([static])
EC50 other aquatic organisms 2	0.031 - 0.054 mg/l (Exposure time: 96 h - species: Pseudokirchneriella subcapitata[static])
Barium Carbonate (CAS No) 513-77-9	
LC50 fishes 1	6950 mg/l - (Exposure time: 96 h - species: Gambusia affinis)
Sodium silicate (CAS No) 1344-09-8	
BCF fish 1	(no bioaccumulation expected)
Calcium Carbonate (CAS No) 1317-65-3	
BCF fish 1	(no bioaccumulation expected)
Calcium Fluoride (CAS No) 7789-75-5	
BCF fish 1	(no bioaccumulation expected)
Graphite (CAS No) 7782-42-5	
LC50 fishes 1	100 mg/l - (Exposure time: 96 h - species: Danio rerio)
EC50 Daphnia 1	100 mg/l (Exposure time: 48 h - species: Daphnia magna [static])
Iron (CAS No) 7439-89-6	
LC50 fishes 1	0.56 mg/l (Exposure time: 96 h - species: Cyprinus carpio [semi-static])
Tin (CAS No) 7440-31-5	
BCF fish 1	(no bioaccumulation expected)

12.2 Persistence and degradability: No additional information available.

12.3 Bioaccumulative potential: No additional information available.

12.4 Mobility in soil: No additional information available.

12.5 Other adverse effects: No additional information available.

## SECTION: 13 DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods: Dispose of in accordance with local and national regulations.

Waste disposal recommendations: Dispose of contents/container in accordance with local/regional/national/international regulations.

## SECTION: 14 TRANSPORT INFORMATION

In accordance with DOT / ADR / RID / ADNR / IMDG / ICAO / IATA


14.1 UN Number: Not a dangerous good in sense of transport regulations

14.2 UN proper shipping name: Not applicable

## SECTION: 15 REGULATORY INFORMATION

15.1 US Federal Regulations:

Copper	(CAS No) 7440-50-8
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
Listed on SARA Section 313 (Specific toxic chemical listings)	
SARA Section 313 - Emission Reporting 1.0%	
Barium Carbonate	(CAS No) 513-77-9
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
Sodium silicate	(CAS No) 1344-09-8
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
Calcium carbonate	(CAS No) 1317-65-3
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
Calcium fluoride	(CAS No) 7789-75-5
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
Graphite	(CAS No) 7782-42-5
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
Iron	(CAS No) 7439-89-6
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	
Tin	(CAS No) 7440-31-5
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	

 **WARNING:** This product can expose you to chemicals including **Chromium (hexavalent compounds)**, which is known to the State of California to cause cancer, and **Carbon monoxide**, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

### Supplemental Safety Guidance Documents

Please refer to the following supplemental safety guidance documents for additional information:

American National Standard, Safety in Welding, Cutting and Allied Processes Guidance (American National Standard Z49.1)  
[https://app.aws.org/technical/AWS\\_Z49.pdf? ga=2.92930778.674520871.1541095810-1419732123.1541007130](https://app.aws.org/technical/AWS_Z49.pdf? ga=2.92930778.674520871.1541095810-1419732123.1541007130)

American Welding Society, Safety and Health Fact Sheets (All topics)  
<https://www.aws.org/standards/page/safety-health-fact-sheets>

American Welding Society, Safety and health fact sheet – Fumes and Gases  
<https://www.aws.org/library/doclib/fs1-201410.pdf>

American Welding Society, Health effects from Welding Exposures  
<https://www.aws.org/library/doclib/AWS-LiteratureUpdate-2016.pdf>

OSHA Technical Manual, Section III, Chapter 3, Ventilation Investigation  
[https://www.osha.gov/dts/osta/otm/otm\\_iii/otm\\_iii\\_3.html](https://www.osha.gov/dts/osta/otm/otm_iii/otm_iii_3.html)

# 2300 Phosphor Bronze Electrodes

## SAFETY DATA SHEET 8 of 9



### 15.2 US State Regulations:

Copper (CAS No) 7440-50-8				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. California - Proposition 65 - Reproductive Toxicity - Female	U.S. California - Proposition 65 - Reproductive Toxicity - Male	No Significance risk level (NSRL)
Yes				
Barium Carbonate (CAS No) 513-77-9				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. California - Proposition 65 - Reproductive Toxicity - Female	U.S. California - Proposition 65 - Reproductive Toxicity - Male	No Significance risk level (NSRL)
Yes	Yes	Yes	Yes	Yes
Sodium silicate (CAS No) 1344-09-8				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. California - Proposition 65 - Reproductive Toxicity - Female	U.S. California - Proposition 65 - Reproductive Toxicity - Male	No Significance risk level (NSRL)
Yes				
Calcium carbonate (CAS No) 1317-65-3				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. California - Proposition 65 - Reproductive Toxicity - Female	U.S. California - Proposition 65 - Reproductive Toxicity - Male	No Significance risk level (NSRL)
Yes				
Calcium fluoride (CAS No) 7789-75-5				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. California - Proposition 65 - Reproductive Toxicity - Female	U.S. California - Proposition 65 - Reproductive Toxicity - Male	No Significance risk level (NSRL)
Yes				
Graphite (CAS No) 7440-50-8				



# 2300 Phosphor Bronze Electrodes

## SAFETY DATA SHEET 9 of 9

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. California - Proposition 65 - Reproductive Toxicity - Female	U.S. California - Proposition 65 - Reproductive Toxicity - Male	No Significance risk level (NSRL)
Yes				
Iron (CAS No) 7439-89-6				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. California - Proposition 65 - Reproductive Toxicity - Female	U.S. California - Proposition 65 - Reproductive Toxicity - Male	No Significance risk level (NSRL)
Yes				
Tin (CAS No) 7440-31-5				
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. California - Proposition 65 - Reproductive Toxicity - Female	U.S. California - Proposition 65 - Reproductive Toxicity - Male	No Significance risk level (NSRL)
Yes				



**SECTION: 16 OTHER INFORMATION**


Full text of H-phrases:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Acute Tox. Not Classified (Oral)	Acute toxicity (oral), Not classified
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard, Category 1
Carc. 1A	Carcinogenicity, Category 1A
Carc.2	Carcinogenicity, Category 2
Repr.1A	Reproductive toxicity, Category 1A
STOT RE 2	Specific target organ toxicity - Repeated exposure, Category 2

H302	Harmful if swallowed
H332	Harmful if inhaled
H350	May cause cancer
H351	Suspected of causing cancer

H360	May damage fertility of the unborn child
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

NFPA health hazard: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.  
NFPA fire hazard: 0 - Materials that will not burn.  
NFPA reactivity: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health: 2 - Moderate Hazard - Temporary or minor injury may occur  
Flammability: 0 - Minimal Hazard  
Physical: 0 - Minimal Hazard

We believe that the information contained herein is believed to be true and accurate as of the date of this SOS. All statements or suggestions are made without any warranty, expressed or implied, regarding the accuracy of the information, the hazard connected with the use of this material or the results to be obtained for use thereof. As the condition or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for any use of this material. It is the user's obligation to determine the conditions of safe use of these products.

All chemical products can in fact present unknown risks to health, safety and / or the environment, even in relation to the different operating conditions, and they must therefore be used with care. For this reason we cannot guarantee that the risk described in this form are the only foreseeable risks. The user must therefore satisfy himself as to the particular conditions under which it is intended to be use in. Moreover, it must be noted that the user is obliged to comply with all the legislative, administrative and regulatory provisions regarding the product and its use in terms of occupational hygiene and safety, and environmental protection, apart from the information given in the form, given purely as guidance.

Technical Department

